



# **NEW!** Meeting ALL Kerosene Needs

*Efficient kerosene  
construction heat*



## **SMALL CAPACITY - Tradesman K45 / K75**

**Features Include:**

- Comfort control T-stat (K75)
- LED power indicator
- Lift handle
- Fuel gauge
- Spark ignition
- Cord wrap
- Safety flameout sensor
- High limit safety sensor
- Built in air pressure gauge



45,000 btu/h & 75,000 btu/h

## **MEDIUM CAPACITY - Tradesman K125 / K170 / K210**

**Features Include:**

- Comfort control T-stat
- Room temperature display
- Digital diagnostics
- Front and rear lift handles
- Fuel gauge
- Spark ignition
- Safety flameout sensor
- High limit safety sensor
- Cord wrap
- Auxiliary power outlet
- Pneumatic wheels
- Built in air pressure gauge



125,000 btu/h & 170,000 btu/h & 210,000 btu/h

## **LARGE CAPACITY - Tradesman K400 / K650**

**Features Include:**

- Comfort control T-stat
- Room temperature display
- Digital Diagnostics
- Front and rear lift handles
- Fuel gauge
- Safety flameout sensor
- High limit safety sensor
- Cord wrap (400K)
- Pneumatic wheels (400K)
- Solid rubber wheels (650K)



400,000 btu/h & 650,000 btu/h

# Tradesman® K Heater Specifications

	Tradesman K45	Tradesman K75	Tradesman K125	Tradesman K170	Tradesman K210	Tradesman K400	Tradesman K650
<b>Btu/h Rating:</b>							
<b>Maximum Input</b>	45,000	75,000	125,000	170,000	210,000	400,000	650,000
<b>Heated Air Output (CFM):</b>	175	265	520	600	650	1400	3600
<b>Pump Pressure (PSI):</b>	2.8	3.8	5.5	6.5	8.5	125	110
<b>Fuel Consumption (max.):</b>							
<b>Kerosene or     #1 or #2 Fuel Oil (gal./hr.)</b>	0.35	0.57	0.95	1.3	1.6	3.0	4.9
<b>Tank Capacity (gal.):</b>	5	5	10	13	13	29	50
<b>Operating Time/Tankful (hrs.):</b>	14	8.8	10.5	10	8	9.5	10
<b>Ignition Type:</b>	Direct Spark	Direct Spark	Direct Spark	Direct Spark	Direct Spark	Direct Spark	Direct Spark
<b>Electrical Supply (V / Hz / Ph):</b>	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1	120 / 60 / 1
<b>Amps (Cont. Oper.)</b>	1.6	1.6	2.5	3.2	3.7	4.4	7.1
<b>Motor Horsepower</b>	1/8	1/8	1/5	1/4	1/3	1/2	3/4
<b>Case Material:</b>	Baked Enamel	Baked Enamel	Baked Enamel	Baked Enamel	Baked Enamel	Baked Enamel	Baked Enamel
<b>Dimensions (in.): *</b>							
<b>Length</b>	32.0	32.0	37.5	43.5	43.5	52.5	69.2
<b>Width</b>	11.75	11.75	22.4	23.9	23.9	32.0	30.7
<b>Height</b>	16.75	16.75	24.9	26.6	26.6	34.0	48.7
<b>Net Weight (lbs. – w/o fuel):</b>	27	27	52	56	62	141	276
<b>Shipping Weight (lbs.):</b>	30	30	58	65	69	155	298
<b>Thermostat:</b>	–	S	S	S	S	S	S
<b>Handle(s):</b>	S	S	S	S	S	S	S
<b>Wheels:</b>	–	–	S	S	S	S	S
<b>Fuel &amp; Pump Pressure Gauges:</b>	S / S	S / S	S / S	S / S	S / S	S / -	S / -
<b>On/Off Switch:</b>	S	S	S	S	S	S	S
<b>Cord Caddy:</b>	S	S	S	S	S	S	–
<b>CSA US &amp; Canada Certification:</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes

\* Dimensions are for fully assembled units with wheels and handles.

S = Standard



Quality heaters you can count on.

Your L.B. White Dealer:

W6636 L.B. White Rd., Onalaska, WI 54650

(800) 345-7200

(608) 783-5691

(608) 783-6115, fax

[www.lbwhite.com](http://www.lbwhite.com)

© 2009 L.B. White Co.  
All rights reserved.  
All specifications are subject  
to change without notice.

F#5103.0409